NINJA® ZX™-10R









POWER

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 13.0:1

Maximum Horsepower 196.0 hp1 @ 11,500 rpm

Fuel System DFI® with 47mm throttle bodies

Ignition TCBI with Digital Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Öhlins Electronic Steering Damper, Electronic Cruise Control, Power Modes, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Balance Free gas-charged shock, adjustable compression damping, adjustable rebound damping, stepless adjustable spring preload/4.5 in Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Brembo dual semi-floating 330mm discs with dual

radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

(ABS only)

Rear Brakes Single 220mm disc with aluminum single-piston

caliper, Kawasaki Intelligent anti-lock Brake System

(KIBS) (ABS only)

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 25.0°/4.1 in

Overall Length 82.1 in

Overall Width 29.5 in

Overall Height 46.7 in

Ground Clearance 5.3 in

Seat Height 32.9 in

Curb Weight 456.4 lb* (ABS), 452.0 lb* (non-ABS)

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Metallic Flat Spark Black/Ebony

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. @2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit mexico.kawasaki-la.com for full product details.