

2026

BRUTE FORCE® 450 4x4

Kawasaki
Let the Good Times Roll®



- AZUL GRISÁCEO
- ROJO FIRECRACKER



POTENCIA

Motor	4-stroke, single-cylinder, SOHC, liquid-cooled
Cilindrada	443cc
Diámetro por carrera	89.0 x 71.2mm
Relación de compresión	9.1:1
Potencia máxima	32.0 hp ¹ @ 7,000 rpm
Par motor máximo	24.6 lb-ft @ 6,500 rpm
Sistema de combustible	FI with 38mm throttle body
Encendido	Digital DC-CDI
Transmisión	Automatic Continuously Variable Transmission (CVT) with centrifugal clutch (H,L,N,R)
Transmisión final	Selectable 2WD/4WD with dual-mode front differential, shaft

CAPACIDAD

Suspensión delantera/ recorrido del neumático	Dual A-arm, adjustable spring preload/7.6 in
Suspensión trasera/ recorrido del neumático	Dual A-arm, adjustable spring preload/7.9 in
Neumáticos delanteros	AT 24 x 8-12
Neumáticos traseros	AT 24 x 10-12
Frenos delanteros	Dual 202mm discs
Frenos traseros	Single 202mm disc
Distancia al suelo	9.3 in
Arranque	Electric

Depósito de combustible	4.2 gal
Steering	Conventional tie-rod
Radio de giro	10.2 ft
Capacidad de remolque	1,050 lb
Capacidad total de las parrillas	225 lb
Capacidad total de las parrillas	75/150 lb
Faros	LED headlights, LED handlebar mounted light, Halogen taillight

DETALLES

Tipo de chasis	Double-cradle, high-tensile tubular steel
Tread Width	35.8/34.2 in
Largo total	80.1 in
Ancho total	43.3 in
Altura total	46.7 in
Altura del asiento	34.6 in
Peso seco estimado	648.3 lb** / 650.5 lb** CA Model
Peso en orden de marcha	688.0 lb* / 690.2 lb* CA Model
Distancia entre ejes	47.8 in
Instrumental	Speedometer, tachometer, gear position indicator, fuel gauge, clock, odometer, hour meter, trip meter, Differential Lock/4WD indicator, etc.
Special Features	KQR™ system-compatible front and rear cargo racks
Colores disponibles	Grayish Blue, Firecracker Red
Garantía	Garantía limitada de 12 meses

Escanear con cámara para ver videos, características clave y más.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visite mexico.kawasaki-la.com para obtener detalles completos del producto.